

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

1-26. (canceled)

27. (currently amended) A tray system for holding and positioning head suspensions as components, the tray system comprising:

a first tray comprising a first side having at least one component receptacle and an opposite second side having at least one component receptacle, wherein at least one of the component receptacles of the first side of the first tray comprises a base plate seat positioned adjacent a first load beam seat, and at least one of the component receptacles of the second side of the first tray comprises a base plate collar seat adjacent a second load beam seat; and

a second tray engageable with the first tray, the second tray comprising a first side having at least one component receptacle and an opposite second side having at least one component receptacle, wherein at least one of the component receptacles of the first side of the second tray comprises a base plate seat positioned adjacent a first load beam seat, and at least one of the component receptacles of the second side of the second tray comprises a base plate collar seat adjacent a second load beam seat,

wherein the second side of the first tray is adjacent the first side of the second tray so that the at least one component receptacle of the first side of the second tray is substantially aligned with the at least one component receptacle of the second side of the first tray for cooperatively restraining the motion of at least one component, of the components, positioned therein.

28. (previously presented)The tray system of claim 27, further comprising at least one opening extending from the component receptacle on the first side of the first tray to the component receptacle on the second side of the first tray.

29. (previously presented)The tray system of claim 28, further comprising a vacuum chamber in fluid communication with the opening of the first tray.

30. (canceled)

31. (canceled)

32. (previously presented) The tray system of claim 27 ~~31~~, wherein at least one of the base plate seats of the second tray includes a component engaging protuberance, wherein the protuberance is engageable with the base plate collar seat of the adjacent first tray.

33. (previously presented) The tray system of claim 27 ~~31~~, wherein at least one of the base plate collar seats of the first tray includes a component engaging recess, wherein the recess is engageable with the base plate seat of the adjacent second tray.

34. (previously presented) The tray system of claim 27 ~~30~~, wherein the first load beam seat further comprises at least one upwardly extending portion for laterally restraining a component positioned thereon.

35. (previously presented) The tray system of claim 27 ~~30~~, wherein the base plate collar seat further comprises a collar relief aperture for receiving a collar portion of a component.

36. (previously presented) The tray system of claim 27 ~~31~~, wherein the second load beam seat further comprises at least one upwardly extending portion for laterally restraining a component positioned thereon.

37. (previously presented) The tray system of claim 27 ~~30~~, wherein the first load beam seat further comprises at least one opening extending from the first side of the first tray to the second side of the first tray.

38. (previously presented) The tray system of claim 27 ~~31~~ in combination with at least one component.

39. (canceled)

40. (previously presented) The tray system of claim 27, wherein the first tray and second tray are identical.

Claims 41-48 (canceled).